Technical Data Sheet

SCHROEDER DIFFUSOR

FINISH : PAINTING, WOOD, FABRICS

The **SCHROEDER DIFFUSOR** is a quadratic residue diffusor. Placed on walls, it reduces floating echoes, and homogenizes the reverberant field.

COMPOSITION:

Made from Medium Density Fiberboard, the diffusors are available several dimensions (according to desired frequency in bandwidths), and with different finishes (wood, painting, lacquered, fabrics).

ADVANTAGES:

- Very high acoustic diffusion on frequency bandwidth. -
- Improvement of hearing comfort (reduction of tunnel effect, virtual widening of the room).
- Echoes and bad reflections reduction.
- Several finishes available : fabrics, paintings, wood. _
- Wall or flush mounting.
- M3 fire-retardant.

Standard thickness :

Dimensions :

Fire-retardant :

Finish :

Weiaht :

TECHNICAL DATAS:

600 x 1200 mm and 1200 x 1200 mm - any size on request 150, 200, or 250 mm Any wood species or paintings (mat, satin, lacquer). approximately 40 kg for a '1200 x 1200 mm' diffusor. М3

> 0.3 0.2

0.1

ACOUSTIC PERFORMANCES:

Diffusion The SCHROEDER DIFFUSOR brings an omnidirectional diffusion or a wide frequency bandwidth. Its goals : beel 0.5 - Improvement of listening rooms acoustics. Ē 0.4


- Flutter echoes reduction.
- Increasing the room liveness.

INSTALLATION:

The SCHROEDER DIFFUSORS are placed vertically, or horizontally, with invisible hooks.

APPLICATIONS:

- Control-rooms, home-studios.
- Auditoriums.
- Recording studios.
- Movie theaters, home-cinemas.
- Conference rooms.



f(Hz)

dB MUTE SPRL - SOUNDPROOFING AND ROOM ACOUSTICS - STUDIES / PROJECTS / MATERIALS 57, rue de Theux B-1040 Bruxelles Tél. +32(0)2 538.63.10 Fax. +32(0)2 538.81.39 e-mail: info@dbmute.com Website : www.dbmute.com - TVA 873.201.720 - Nº enr. 03/16/01 - ING 310-1890717-79



